



## INSTALLATION INSTRUCTIONS

### IGNITE MOTORCYCLE KIT

**Always disconnect any power sources connected to your vehicle before servicing fuses or electrical systems. Professional installation is recommended.**

**Note: When selecting light location, consider wire routing and range of motion of front wheel. If a fork or freeway bar mount location is desired.**

1. Mark and drill holes for install, use 1/4" drill bit
2. Install lights using provided hardware.
3. Select switch location, mount using provided radius mount pad and zip ties, or double sided adhesive tape.
4. Wiring: Route wire leads, switch wire leads and harness. Trim excess wire, secure to bike using zip ties. Take care to avoid any heat sources & sharp or abrasive surfaces.
5. Reconnect power source, point bike at wall to aim lights. To toggle between high and low modes, turn the switch off and on quickly (within 3 seconds).

### WARRANTY INFORMATION

For warranty information, visit [www.rigidindustries.com/about/warranty](http://www.rigidindustries.com/about/warranty)  
779 N Colorado St, Gilbert, AZ 85233 • 855-760-5337

[www.rigidindustries.com](http://www.rigidindustries.com)

Ignite and Rigid Industries are registered and/or common law marks owned by JST Performance, LLC, a Delaware limited liability company d/b/a Rigid Industries.